

CERTIFICATE OF COMPLIANCE

Certificate Number 20190520-E345867
Report Reference E345867-20150610
Issue Date 2019-MAY-20

Issued to: ADVANCED LIGHTING CONCEPTS INC, DBA
ENVIRONMENTALLIGHTS.COM
SUITE 102
11235 W BERNARDO CT
SAN DIEGO, CA 92127 USA

**This certificate confirms that
representative samples of**

LOW-VOLTAGE LIGHTING SYSTEMS, POWER UNITS,
LUMINAIRES AND FITTINGS
See Addendum Pages

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety:

UL1598 & CSA-C22.2 No. 250.0 - Luminaires
UL 2108 - Low Voltage Lighting Systems
UL 8750 - Light Emitting Diode (LED) Equipment for Use in
Lighting Products


Additional Information:

See the UL Online Certifications Directory at
<https://iq.ulprospector.com> for additional information.

This *Certificate of Compliance* does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number 20190520-E345867
Report Reference E345867-20150610
Issue Date 2019-MAY-20

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Low voltage, non-dimmable Class 2 LED surface-mount luminaires, panel type indoor use only, Model(s) EL-PR24V-XX (Round), EL-PS24V-XX (Square)

Low voltage, non-dimmable Class 2 LED surface-mount luminaires, strip type, Model(s) EL-12V-Y-XX, EL-24V-Y-XX

Low voltage, non-dimmable Class 2 LED surface-mount luminaires, strip type suitable for outdoor use, Model(s) EL-12V-Z-XX, EL-24V-Z-XX


XX - Where XX represents color of LED.

Low Voltage, Dimmable, Class 2 LED Recessed or Surface-Mount Luminaires, Flexible type, Model(s) EL-PL180X180X-DS, EL-PL240X240X-DS, EL-PL300X300X-DS, EL-PL300X600C-DB, EL-PL300X600TH-DB, EL-PL600X600C-DB, EL-PL600X600TH-DB, EL-PR240X-DS, EL-PR300X-DS, X-F2835HYZ-G-12W-V, X-F2835HYZ-G-24W-V, X-F3020HYZ-G-12W-V, X-F3020HYZ-G-24W-V, X-F335HYZ-G-12W-V, X-F335HYZ-G-24W-V, X-F3528HYZ-G-12W-V, X-F3528HYZ-G-24W-V, X-F3535HYZ-G-12W-V, X-F3535HYZ-G-24W-V, X-F5050HYZ-G-12W-V, X-F5050HYZ-G-24W-V, X-F5050HYZ-G-5W-V, X-F5630HYZ-G-12W-V, X-F5630HYZ-G-24W-V

Low Voltage, Dimmable, Class 2 LED Recessed or Surface-Mount Luminaires, Panel type, suitable to dry or damp locations, Model(s) EL-PL200X200X-DB2, EL-PL240X240X-DB2, EL-PL300X1200X-DB, EL-PL300X1200X-DC, EL-PL300X300X-DB, EL-PL300X300X-DB2, EL-PL300X300X-DC, EL-PL300X600X-DB, EL-PL300X600X-DC, EL-PL600X1200X-DB, EL-PL600X600X-DB, EL-PL600X600X4-DB, EL-PL600X600X4-DC, EL-PL620X620X-DB, EL-PL620X620X4-DB, EL-PR145X-DB2, EL-PR180X-DB2, EL-PR180X-DS, EL-PR240X-DB2, EL-PR300X-DB2

Low Voltage LED Luminaire, Surface Mounted LED low-voltage Luminaires, Model(s) X-zxxxxHYZ-G-yW-V(a)

- (a) - X denotes series Designation, may be EL, SA or LH for marketing purpose. z denotes Type of Low Voltage Luminaires, it can be "F" = flexible type, "M" = Rigid Type. xxxx denote the type of LED chip, it can be "5050", "3528", "2835", "3020", "5630", "335", "2216", "3535", "5730", "3014", "4014", "3030", "2525", "2016", "020", "0603", "0805", "1206". H can be: A denotes for Damp location; B "C" "D" "S" which denotes for Wet location.. Y = LED chip per section(half meter). Z = Can be TSA or SA or left blank. TSA also can be T or TS, which Denotes changeable Color temperature. SA also can be S? SL, SAL, or L, which denotes the Index of Color Rendering or Brightness respectively. G = Can be any number or letter combination to refer to the color. y = Denotes input voltage, it can be 12V or 24V. W = Can be C, CC, DMX, or left blank which denotes constant current or DMX control signal respectively. V = Can be any number or letter combination or left blank for business purpose.



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

