

# LiteLinks LED Light Bar



## Seamless Light & Custom Configurations

LiteLinks are ultra-bright LED lightbars that link together to create UL Listed lighting solutions. Built-in diffusers run to the edge of each bar and provide seamless distribution of light across connections. LiteLinks need no cutting or soldering. Simply remove the end caps and connect the two bars together. Integrated mounting magnets reduce installation time by securely adhering to metal surfaces without the need for additional hardware. LiteLinks are the ideal solution for lighting retail product displays such as gondolas and endcaps.

- Available in 3,000K, 4,000K and 5,000K
- Available in lengths of 100mm or 300mm and in corner pieces
- Channel, strip light and diffuser in one complete package
- Magnetic mounting
- High brightness
- Linkable up to 3 meters
- UL Listed



# LiteLinks LED Light Bar

## Specifications

	LiteLinks LED Light Bar - 3000K - CurrentControl - 300mm 3000K-CC2835LL-LB-63-11-300	LiteLinks LED Light Bar - 4000K - CurrentControl - 300mm 4000K-CC2835LL-LB-63-11-300	LiteLinks LED Light Bar - 5000K - CurrentControl - 300mm 5000K-CC2835LL-LB-63-11-300
Brightness (lm/m)	1,560	1,620	1,690
Power (W)	6.2	6.2	6.2
CRI	80+	80+	80+
CCT	3,000K	4,000K	5,000K
Beam Angle	120°	120°	120°
Length (mm)	310	310	310
Width (mm)	11	11	11
Height (mm)	11.8	11.8	11.8
Input Voltage (V AC)	24	24	24
Input Current (mA)	258	258	258
Rating	UL Listed,CE,RoHS	UL Listed,CE,RoHS	UL Listed,CE,RoHS
IP Rating	IP20	IP20	IP20
Warranty	3 year limited	3 year limited	3 year limited

# LiteLinks LED Light Bar

## Specifications

	LiteLinks LED Light Bar - 3000K - CurrentControl - 100mm 3000K-CC2835LL-LB-21-11-300	LiteLinks LED Light Bar - 4000K - CurrentControl - 100mm 4000K-CC2835LL-LB-21-11-300	LiteLinks LED Light Bar - 5000K - CurrentControl - 100mm 5000K-CC2835LL-LB-21-11-300
Brightness (lm/m)	1,560	1,620	1,690
Power (W)	2	2	2
CRI	80+	80+	80+
CCT	3,000K	4,000K	5,000K
Beam Angle	120°	120°	120°
Length (mm)	110	110	110
Width (mm)	11	11	11
Height (mm)	11.8	11.8	11.8
Input Voltage (V AC)	24	24	24
Input Current (mA)	83	83	83
Rating	UL Listed,CE,RoHS	UL Listed,CE,RoHS	UL Listed,CE,RoHS
IP Rating	IP20	IP20	IP20
Warranty	3 year limited	3 year limited	3 year limited

# LiteLinks LED Light Bar

## Specifications

	LiteLinks LED Light Bar - 3000K - CurrentControl - Corner A 3000K-CC2835LL-CA	LiteLinks LED Light Bar - 4000K - CurrentControl - Corner A 4000K-CC2835LL-CA	LiteLinks LED Light Bar - 5000K - CurrentControl - Corner A 5000K-CC2835LL-CA
Brightness (lm/m)	1,560	1,620	1,690
Power (W)	3.4	3.4	3.4
CRI	80+	80+	80+
CCT	3,000K	4,000K	5,000K
Beam Angle	120°	120°	120°
Length (mm)	83	83	83
Width (mm)	20	20	20
Height (mm)	11.8	11.8	11.8
Input Voltage (V AC)	24	24	24
Input Current (mA)	142	142	142
Rating	UL Listed,CE,RoHS	UL Listed,CE,RoHS	UL Listed,CE,RoHS
IP Rating	IP20	IP20	IP20
Warranty	3 year limited	3 year limited	3 year limited

## Corner A



# LiteLinks LED Light Bar

## Specifications

	LiteLinks LED Light Bar - 3000K - CurrentControl - Corner B	LiteLinks LED Light Bar - 4000K - CurrentControl - Corner B	LiteLinks LED Light Bar - 5000K - CurrentControl - Corner B
	3000K-CC2835LL-CB	4000K-CC2835LL-CB	5000K-CC2835LL-CB
Brightness (lm/m)	1,560	1,620	1,690
Power (W)	3.4	3.4	3.4
CRI	80+	80+	80+
CCT	3,000K	4,000K	5,000K
Beam Angle	120°	120°	120°
Length (mm)	83	83	83
Width (mm)	20	20	20
Height (mm)	11.8	11.8	11.8
Input Voltage (V AC)	24	24	24
Input Current (mA)	142	142	142
Rating	UL Listed,CE,RoHS	UL Listed,CE,RoHS	UL Listed,CE,RoHS
IP Rating	IP20	IP20	IP20
Warranty	3 year limited	3 year limited	3 year limited

## Corner B

