JAZ Extrusion Ref. A08547





TECHNICAL DRAWING



Wide lighting angle

Intertek

Hardly visible aluminum elements

CLOSET RATEE

- Lighting fixture with round cross-section
- Wide range of accessories

APPLICATION


- main and decorative lighting

MOUNTING

- suspended, using dedicated accessories
- can be easily connected into runs and systems

ADDITIONAL INFORMATION

- standard lengths of KLUŚ profiles and covers: 1000 mm (tolerance \pm 1.5 mm) and 2005 mm / 3010 mm (tolerance + 5 mm); for selected covers: 6050 mm, 10050 mm (tolerance + 5 mm)
- when choosing a different length of profiles / covers than available in the standard, you should additionally choose the cutting service at KLUS



TECHNICAL SPECIFICATIONS


| Material | aluminum | |
|---|---|--|
| Color | silver anodized | |
| Possible fixture IP | 20 | |
| Possible fixture shapes | linear, polygonal | |
| Profile cross-section | round | |
| Width | 0.9" | |
| Height | 0.3" | |
| LED gluing width A | 0.8" | |
| Number of LED strips A (0.31" wide) | 2 | |
| Width of the glow | 22.8 mm | |
| Max power of a single KLUŚ LED strip | 24 W/m | |
| Possibility of obtaining a line of light | yes | |
| Building type | Entertainment/ Arts, Commercial, Hotel / Restaurant Residential | |
| Facility zone | office, conference room, lobby / foyer, inne | |
| The cover is cut to the length of the profile | yes | |
| Can be easily connected into runs | yes | |

| Length | Ref |
|--------|-----------|
| 39.4" | A08547A_1 |
| 78.9" | A08547A_2 |
| 118.5" | A08547A_3 |





TECHNICAL DRAWING



TECHNICAL SPECIFICATIONS

| Finish | satin | Length | Ref |
|--|--------|--------|-----------|
| Material | PC | 39.4" | B171625_1 |
| Shape | round | 78.9" | B171625_2 |
| Maximum length on request | 236.2" | 118.5" | B171625_3 |
| Light transmission | 78 % | | |
| Width | 1.2" | | |
| Possibility of obtaining a line of light | yes | | |

RELATED PROFILES > ARCHITECTURAL



JAZ A08547

- Excellent light dispersion
- Made of PC with increased resistance to weather conditions

APPLICATION

- LED protection and light diffusion in lighting fixtures

MOUNTING

- Snapped in a dedicated profile


ADDITIONAL INFORMATION

- ATTENTION! rigid cover, not intended for bending or deformation
- standard lengths of KLUŚ profiles and covers: 1000 mm (tolerance \pm 1.5 mm) and 2005 mm / 3010 mm (tolerance + 5 mm); for selected covers: 6050 mm, 10050 mm (tolerance + 5 mm)
- when choosing a different length of profiles / covers than available in the standard, you should additionally choose the cutting service at KLUŚ





TECHNICAL DRAWING



TECHNICAL SPECIFICATIONS

| Material | PP | Width | 1.18" |
|----------|-------|---------------------------------------|----------|
| Color | gray | Corrosion resistance | yes |
| Shape | round | Corrosion resistance at high salinity | yes |
| Height | 1.18" | | <u>.</u> |



APPLICATION

- aesthetic finish and protection of the interior of the lighting fixture

MOUNTING

- to the extrusion, by pressing

