

CERTIFICATE OF COMPLIANCE

Certificate Number 20190321-E345867
Report Reference E345867-20150515
Issue Date 2019-MARCH 21

Issued to: ADVANCED LIGHTING CONCEPTS INC, DBA
ENVIRONMENTALLIGHTS.COM
SUITE 102
11235 W BERNARDO CT
SAN DIEGO, CA 92127 USA

**This is to certify that
representative samples of**

LOW-VOLTAGE LIGHTING SYSTEMS, POWER UNITS,
LUMINAIRES AND FITTINGS
See Addendum Page

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety:

UL 2108, Low Voltage Lighting Systems;
UL 8750, Light Emitting Diode (LED) Equipment for Use in
Lighting Products;
CSA-C22.2 No. 250.0, Luminaires;
CSA-C22.2 No. 9.0, General Requirements for Luminaires

Additional Information:

See the UL Online Certifications Directory at
www.ul.com/database for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's
Certification and Follow-Up Service.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please
contact a local UL Customer Service Representative at <http://ul.com/about/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number 20190321-E345867
Report Reference E345867-20150515
Issue Date 2019-MARCH 21

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Evaluated to UL 2108, UL 8750 and CSA-C22.2 No. 250.0:

Low Voltage LED rigid bar, surface mounted: Models EL-Bar-PI-12V-X, EL-Bar-PO-24V-X, EL-Bar-PI-24V-X, EL-Bar-EI-12V-X, EL-Flex-O-12V-X, EL-Flex-I-12V-X, EL-Flex-O-24V-X, EL-Flex-I-24V-X, EL-Flex-PO-12V-X, EL-Flex-PI-12V-X, EL-Flex-PO-24V-X, EL-Flex-PI-24V-X, EL-Flex-EI-12V-X, EL-Bar-O-12V-X, EL-Bar-I-12V-X, EL-Bar-PO-12V-X, where "X" can be any alphanumeric character.

Low Voltage LED Tape Light, surface mounted: Models EL-Flex-L-X, EL-Flex-T-X, EL-Flexs-12V-X, EL-Flex-KR-X, EL-Flex-HD-X, EL-Flex-SV-12V-X, EL-Flex-SV-24V-X, EL-MSW6-X, EL-MDW6-X, where "X" can be any alphanumeric character.

Low Voltage LED Surface-Mounted Light: Models EL-FlexSV-O-24-BB (a), EL-Flexs-I-24-BB (a), EL-FG-I-24-BB (a), EL-Sflex-FI-24-BB (a), EL-Flex-FI-24-BB (a), EL-YD7-L-Y-BB (a), EL-YD8-L-Y-BB (a), EL-Flex-EI-24-BB (a), EL-FlexCC-I-24-BB (a), EL-9Flex-O-24-BB (a), EL-9Flex-I-24-BB (a), EL-Dflex-I-12-BB (a), EL-Dflex-O-12-BB (a) EL-H150-X (c), EL-CC-Flex-I-X (c), EL-FlexSV-O-12-BB, EL-H25FL-24V-X (c), EL-RGB-I-12V, EL-RGB-O-12V, EL-RGBWN-I-24V, EL-RGBWN-O-24V.

Evaluated to UL 2108 and CSA-C22.2 No. 9.0:

Low Voltage LED Surface-Mounted Light: Models EL-BPS-L-Y-X, EL-SFlex-I-12V-X, where "X" can be any alphanumeric character.

Low Voltage LED Surface-Mounted Light, Models EL-RGB-I-24V (b), EL-RGB-O-24V (b), EL-RGBX-I-24V (b), EL-RGBX-O-24V (b), EL-CCFG-I-24V-X (b), EL-CCFG-O-24V-X (b), EL-DTW-I-X (b), EL-DTW-O-X (b), EL-FGP-I-24V-X (b), EL-FGP-O-24V-X (b), EL-CC-I-24V-X (b), EL-FI-24V-X (b), EL-YD2C-I-L-Y-X (b), EL-KPT8-3-O-X (b), EL-H25B-I-12V-L-Y-X (b), EL-H25FL-I-12V-X (b), EL-H25M-I-12V-X (b).

(a) - Where L can be any alphanumeric characters representing bar length; Y/I/O can be any alphanumeric characters representing LED quantity; X/BB can be any alphanumeric characters representing LED color.

(b) - Where L can be any alphanumeric characters representing bar length, Y can be any alphanumeric characters representing LED quantity, X can be any alphanumeric characters.

(c) - Where "X" can be any alphanumeric characters representing LED color.



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number 20190321-E345867
Report Reference E345867-20150515
Issue Date 2019-MARCH 21

Low Voltage LED Surface-Mounted Light

EL-VE-L-Y-X (a)
EL-VE-M-L-Y-X (a)

- (a) Where X can be any alphanumeric characters, where L represents bar length, can be any alphanumeric characters and Y represents LED quantity, can be any alphanumeric character



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

