

CERTIFICATE OF COMPLIANCE

Certificate Number 20170726-E345867
Report Reference E345867-20161108
Issue Date 2017-JULY-26

Issued to: ADVANCED LIGHTING CONCEPTS INC, DBA
ENVIRONMENTALLIGHTS.COM
SUITE 102
11235 W BERNARDO CT
SAN DIEGO, CA 92127 USA

**This is to certify that
representative samples of**

LOW-VOLTAGE LIGHTING SYSTEMS, POWER UNITS,
LUMINAIRES AND FITTINGS

Low Voltage LED Luminaire, Surface Mounted:
EL-aabbccdddTee-fghi series and EL-PNL-aa-bb series.
See Addendum Page for Model Nomenclature

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL 2108 - Low Voltage Lighting Systems
CSA C22.2 No. 250.0-08 - Luminaires

Additional Information: See the UL Online Certifications Directory at
www.ul.com/database for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's
Certification and Follow-Up Service.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please
contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number 20170726-E345867
Report Reference E345867-20161108
Issue Date 2017-JULY-26

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Model Nomenclature

EL	-	aa	bb	cc	ddd	T	ee	—	f	g	h	i
EL	series Name		-									
aa	color temperature		Any letters or numbers.									
bb	Water proof or Not		"WF" = water-proof, "NF"=Non water-proof.									
cc	input voltage		"12" = 12 Vdc, "24" = 24 Vdc									
ddd	LED number per Meter		"060", "090", "120", "180", "240", "300", "312"									
ee	LED type		"T16" = 2216, "T02" = 3528, "T09" = 2835									
f	LED PWB width		"0" = 10 mm, "2" = 12 mm, "5" = 5 mm, "8" = 8 mm									
g	Single or double row		"A" = Single row, "B" = double row									
h	LED current		"1" = 0-10mA, "2" = 11-20mA, "3" = 21-30mA, "4" = 31-40mA, "5" = 41-50mA, "6" = 51-60mA									
i	Color rendering index		Any letters or numbers.									

EL	-	PNL	-	aa	-	bb
EL-PNL-	series Name		-			
aa	The number of each model		"01", "07", "03", "06", "09", "93", "96", "99", "14", "18", "24", "27", "36"			
bb	input voltage		"12" = 12 Vdc, "24" = 24 Vdc			



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

