

CERTIFICATE OF COMPLIANCE

Certificate Number 20200102-E345867
Report Reference E345867-20170620
Issue Date 2020-JUNE-19

Issued to: ADVANCED LIGHTING CONCEPTS INC, DBA
ENVIRONMENTALLIGHTS.COM
SUITE 102
11235 W BERNARDO CT
SAN DIEGO, CA 92127 USA

**This certificate confirms that
representative samples of**

LOW-VOLTAGE LIGHTING SYSTEMS, POWER UNITS,
LUMINAIRES AND FITTINGS
See Addendum Page for Models

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety:

UL 2108, Low Voltage Lighting Systems
CSA C22.2 No. 250.0-18, Luminaires.


Additional Information:

See the UL Online Certifications Directory at
<https://iq.ulprospector.com> for additional information.

This *Certificate of Compliance* does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number 20200102-E345867
Report Reference E345867-20170620
Issue Date 2020-JUNE-19

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

LED low-voltage luminaires, LED Strip Series, surface mounted, class 2 luminaires:

Model(s) Z-XX-AAAA-2216-120-W-L-12V [a], Z-XX-AAAA-2216-180-W-L-12V [a],
Z-XX-AAAA-2216-240-W-L-12V [a], Z-XX-AAAA-2216-300-W-L-12V [a],
Z-XX-AAAA-2216-420-W-L-12V [a], Z-XX-AAAA-2216-600-W-L-12V [a],
Z-XX-AAAA-2216-120-W-L-24V [a], Z-XX-AAAA-2216-180-W-L-24V [a],
Z-XX-AAAA-2216-240-W-L-24V [a], Z-XX-AAAA-2216-300-W-L-24V [a],
Z-XX-AAAA-2216-420-W-L-24V [a], Z-XX-AAAA-2216-600-W-L-24V [a],
Z-XX-AAAA-2835-120-W-L-12V [a], Z-XX-AAAA-2835-120-W-L-24V [a],
Z-XX-AAAA-2835-180-W-L-24V [a], Z-XX-AAAA-2835-30-W-L-24V [a],
Z-XX-AAAA-2835-360-W-L-24V [a], Z-XX-AAAA-2835-60-W-L-24V [a],
Z-XX-AAAA-3527-120-W-L-12V [a], Z-XX-AAAA-3527-120-W-L-24V [a],
Z-XX-AAAA-3528-120-W-L-12V [a], Z-XX-AAAA-3528-180-W-L-12V [a],
Z-XX-AAAA-3528-240-W-L-12V [a], Z-XX-AAAA-3528-30-W-L-12V [a],
Z-XX-AAAA-3528-60-W-L-12V [a], Z-XX-AAAA-3528-120-W-L-24V [a],
Z-XX-AAAA-3528-180-W-L-24V [a], Z-XX-AAAA-3528-240-W-L-24V [a],
Z-XX-AAAA-3528-30-W-L-24V [a], Z-XX-AAAA-3528-60-W-L-24V [a],
Z-XX-AAAA-5050-60-W-L-12V [a], Z-XX-AAAA-5050-60-W-L-24V [a],
Z-XX-AAAA-5050-60-W-L-12V [a], Z-XX-AAAA-5050-60-W-L-24V [a],
Z-XX-AAAA-2835-180-W-L-12V [a], Z-XX-AAAA-2835-30-W-L-12V [a],
Z-XX-AAAA-2835-60-W-L-12V [a], Z-XX-CC2216M-YY-12V [b], Z-XX-2216M-YY-12V [b],
Z-XX-CC2216M-YY-24V [b], Z-XX-2216M-YY-24V [b], Z-XX-CC2835M-YY-12V [b],
Z-XX-2835M-YY-12V [b], Z-XX-CC2835M-YY-24V [b], Z-XX-2835M-YY-24V [b],
Z-XX-CC3014M-YY-24V [b], Z-XX-3014M-YY-24V [b], Z-XX-335M-YY-12V [b],
Z-XX-335M-YY-24V [b], Z-XX-3527M-YY-12V [b], Z-XX-3527M-YY-24V [b],
Z-XX-CC3528M-YY-12V [b], Z-XX-3528M-YY-12V [b], Z-XX-CC3528M-YY-24V [b],
Z-XX-3528M-YY-24V [b], Z-XX-CC5050M-YY-12V [b], Z-XX-5050M-YY-12V [b],
Z-XX-CC5050M-YY-24V [b], Z-XX-5050M-YY-24V [b], Z-XX-CC5730M-YY-12V [b],
Z-XX-5730M-YY-12V [b], Z-XX-CC5730M-YY-24V [b], Z-XX-5730M-YY-24V [b]

[a] - Where Z can be any alphanumeric or blank denoting waterproof, XX can be any alphanumeric denoting color, AAAA may be any alphanumeric to denote marketing, W may be any alphanumeric denoting width of PCB, L may be any alphanumeric denoting length of PCB.

[b] - Where Z - can be any number or letter combination or left blank to denote waterproof. XX - can be any number or letter combination to refer to the color. M - can be any number or letter combination or left blank to refer to a marketing name. The letters CC, if applicable, can be 5050, 5730, 335, 3528, 3014, 2835, 3527 or 2216. YY - indicates the LEDs/meter.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number 20200102-E345867
Report Reference E345867-20170620
Issue Date 2020-JUNE-19

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Models: EL-xxxx-Sx-CC2110mm-dd-ww-24-Lx, EL-xxxx-Sx-CC3838mm-dd-ww-24-Lx
EL-Axxxx-Sx-CC5050mm-dd-ww-24-Lx, EL-Axxxx-Sx-CC2110mm-dd-ww-24-Lx,
EL-Axxxx-Sx-CC0603mm-dd-ww-24-Lx, EL-xxxx-Sx-CC5050mm-dd-ww-24-Lx

Where A is for LN for neon designation or blank, xxxx represents CCT, can be any alphanumeric characters, Sx represents enclosure shape, can be any alphanumeric characters or blank to indicate profile, CC represents active current regulations, can be CC or blank, XXXX can be any numbers to represent LED package size, mm represents marketing code, dd represents number of LEDs per meter, ww represents width in mm, V represents voltage, can be 5, 12 or 24 volts, L represents reel length, can be any alphanumeric characters to indicate length and unit



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

