

CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-2012690-1
Report Reference E345867-20201230
Date 15-May-2021

Issued to: Advanced Lighting Concepts LLC d.b.a. Environmental Lights
11235 W Bernardo Ct, Suite 102 San Diego, CA
United States 92127

This is to certify that representative samples of IFDR - Low-voltage Lighting Systems, Power Units, Luminaires and Fittings
See Addendum Page for Product Designation(s).

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL 2108, 2nd Ed., Issue Date: 2015-12-07, Revision Date: 2019-12-06

Additional Information: See the UL Online Certifications Directory at <https://iq.ulprospector.com> for additional information

This Certificate of Compliance does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.

B. Mahrenholz

Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>




CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-2012690-1
Report Reference E345867-20201230
Date 15-May-2021

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description
REVI, Followed by MMM-NNN, where MMM may be FF3 or IC3 indicating 3 inches flat frame or IC box, NNN may be R/S1/S2 for round trim/square trim/square trimless options	Recessed Low Voltage Luminaire Mounting Accessories
REVI-LE1, Followed by AAA-BBB-CCC-DDD-EEE-FFF-GGG, where AAA may be 9V, 18V, or 36V indicating nominal voltage in DC, BBB may be any three digit alphanumeric characters indicating single color CCT, CCC may be any alphanumeric characters indicating beam angle or WW for wall wash lens, DDD may be blank or any two digit alphanumeric characters indicating specialty media insert, EEE may be RF/RA/RW/SF/SA/SW indicating baffle shape, FFF may be T3-R/T3-S/T3-2S/T3-3S/TL3-R/TL3-S indicating trim option, and GGG may be W for white or B for black.	LED Recessed Low Voltage Luminaires
REVI-LE1-18V-TW2765, Followed by CCC-DDD-EEE-FFF-GGG, where CCC may be any alphanumeric characters indicating beam angle or WW for wall wash lens, DDD may be blank or any two digit alphanumeric characters indicating specialty media insert, EEE may be RF/RA/RW/SF/SA/SW indicating baffle shape, FFF may be T3-R/T3-S/T3-2S/T3-3S/TL3-R/TL3-S indicating trim option, and GGG may be W for white or B for black.	LED Recessed Low Voltage Luminaires



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

