

CERTIFICATE OF COMPLIANCE

Certificate Number 20160212-E464442
Report Reference E464442-20150413
Issue Date 2016-FEBRUARY-12

Issued to: ADVANCED LIGHTING CONCEPTS INC, DBA
ENVIRONMENTALLIGHTS.COM
SUITE 102
11235 W BERNARDO CT
SAN DIEGO CA 92127

This is to certify that representative samples of LIGHT-EMITTING-DIODE LUMINAIRES, PORTABLE
See Addendum Page

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL 153, Standard for Portable Electric Luminaires.
UL 8750, Light Emitting Diode (LED) Equipment for Use in Lighting Products.
CAN/CSA C22.2 No. 9, Canadian Standard for Portable Luminaires.

Additional Information: See the UL Online Certifications Directory at www.ul.com/database for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's Certification and Follow-Up Service.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number 20160212-E464442
Report Reference E464442-20150413
Issue Date 2016-FEBRUARY-12


This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Models Flexible Type Portable Luminaries: X-F5050HYZ-G-5W-V, X-F5050HYZ-G-12W-V, X-F3528HYZ-G-12W-V, X-F2835HYZ-G-12W-V, X-F5630HYZ-G-12W-V, X-F3020HYZ-G-12W-V, X-F335HYZ-G-12W-V, X-F3535HYZ-G-12W-V, X-F5050HYZ-G-24W-V, X-F3528HYZ-G-24W-V, X-F2835HYZ-G-24W-V, X-F5630HYZ-G-24W-V, X-F3020HYZ-G-24W-V, X-F335HYZ-G-24W-V, X-F3535HYZ-G-24W-V

X denotes series Designation, may be EL, QL, SA or LH for marketing purpose

Models Panel type of Portable Luminaries, suitable to dry or damp locations: QL-PL300X300X-DC, QL-PL300X600X-DC, QL-PL600X600X4-DC, QL-PL300X1200X-DC, QL-PL300X300X-DB, QL-PL300X600X-DB, QL-PL600X600X-DB, QL-PL600X600X4-DB, QL-PL620X620X-DB, QL-PL620X620X4-DB, QL-PL300X1200X-DB, QL-PL600X1200X-DB, QL-PR145X-DB2, QL-PR145X-DC, QL-PR180X-DB2, QL-PR180X-DC, QL-PR240X-DB2, QL-PR240-DC, QL-PR300X-DB2, QL-PR300X-DC, QL-PL200X200X-DB2, QL-PL240X240X-DB2, QL-PL300X300X-DB2, QL-PR180X-DS, QL-PR240X-DS, QL-PR300X-DS, QL-PL145X145X-DC, QL-PL180X180X-DC, QL-PL240X240X-DC, QL-PL180X180X-DS, QL-PL240X240X-DS, QL-PL300X300X-DS, QL-PL300X600C-DB, QL-PL600X600C-DB, QL-PL300X600TH-DB, QL-PL600X600TH-DB

Model prefix QL- may be substituted with model number prefix EL-. The different Model numbers are for marketing reasons but construction is identical



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

