RGB + 3000K 4-in-1 XL PixelControl LED Strip Light - VN RGB3000K-4in1-XLpixelcontrol-60-10-3m-GP

Country of Origin: Vietnam

PRODUCT DESCRIPTION

The RGB + 3000K 4-in-1 XL PixelControl LED Strip Light combines RGB and warm white (3000K) diodes on the same node, delivering richer tones and more vibrant color mixing than standard Pixel LED strips. With three LEDs per pixel, this high-resolution strip enables smoother gradients, more detailed animations, and extended effects over longer runs.

Each 3-meter reel includes 60 individually addressable pixels (60 nodes/meter) and operates on 12 VDC. The strip is 10mm wide and features bare wire leads on both ends for flexible installation. Power injection is recommended every 3 meters.

Fully compatible with our Pixel LED controllers—no DMX decoder required—or integrate into DMX systems using our DMX512 PixelControl Decoder. Directional input is marked with arrows on the strip for proper configuration.

Ideal Application: Ideal choice for illuminating scenic environments, retail spaces, home and commercial construction, and many other applications.

SPE	CIF	FIC.	ΑΤΙ	ON	IS

Product Number	RGB3000K-4in1-XLpixelcontrol-60-10-3m-GP		
Ambient Temperature	-20°C to 45°C		
Average Lifetime	50,000 Hours		
Beam Angle	120°		
Brightness	150/310/70/385 lumens/meter		
Color Detail	RGB + 3000K White		
Density	60 LEDs/meter		
Finish	White		
Height	0.08 in [2 mm]		
Input Current	4750 mA		
Input Voltage	12 DC		
IP Rating	IP20		
Lead Detail	Bare Wire / 200 mm [both ends]		
LED Node Size	5050		
Length	9.84 ft [3 m]		
Min. Cutting Increment	1.97 in [50 mm]		
Power (Watts/ft)	5.8 Watts/ft		
Power (Watts/m)	19 Watts/m		
Regulatory	UL Listed, RoHS		
Warranty	3 Years Limited		
Width	0.39 in [10 mm]		



PRODUCT FEATURES

- 3 LEDs per pixel
- 12 VDC
- 10 mm wide
- 60 Pixels per reel, 0.469 universes per reel
- 57 watts per reel, 19 watts per meter
- Cuttable every 1.97 in, 50 mm
- UCS2904 IC chip
- UL Listed, RoHS Compliant