


ILUMINARC®

ILUMILINE 21g2 IP OPTIC 60x10 RGB Item Number: 01610557

Client: _____

Project: _____

Date: _____ Type: _____



LIGHT SOURCE & OPTICAL SPECIFICATIONS

Light Source: 21 LEDs (7 red, 7 green, 7 blue) 1 W (350 mA)
Light Source Lifespan: 50,000 hours life expectancy based on LED manufacturer's specifications

Installed Optics: 60° x 10°

Beam Angle: 60° x 24°

Field Angle: 99° x 49°

Lumens: 580

Base Illuminance: 43 lux @ 5 m

Efficacy: 19.6 lm/W

Color Temperature Presets: N/A

Minimum Distance to Illuminated Surface: 4 in (92 mm)

CONSTRUCTION & PHYSICAL SPECIFICATIONS

Length: 23.2 in (590 mm)

Width: 3.5 in (89 mm)

Height: 4 in (102 mm)

Weight: 7 lb (3.18 kg)

Color: Brushed aluminum

Ingress Protection Rating: IP67

Housing Material: Cast aluminum

Lens Cover: Impact resistant glass

Installation Orientation: Any

CONTROL SPECIFICATIONS

Control Protocol: USITT DMX-512a

Control Channels: 1, 3, 4 or 7

Operating Modes: Selectable personalities

Solid (1-channel): dimmer

Arc 1 (3-channel): red, green, blue

Arc 1+D (4-channel): dimmer, red, green, blue

Arc Full (7-channel): dimmer, red, green, blue, color macros, strobe, dimming speed

Stand Alone Control: N/A

Remote Addresser: Ilumicode

Data Connection: 11 ft (3.35 m) Waterproof cable

ELECTRICAL SYSTEM SPECIFICATIONS

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

Power and Current: 28 W, 0.405 A @ 120 V

27 W, 0.222 A @ 230 V

Power Supply: Electronic internal

Dimmer: Electronic

Power Linking: N/A

Power Connection: 9 ft (2.74 m) Waterproof cable

THERMAL SPECIFICATIONS

Cooling: Convection

Startup Temperature Range: -4 °F to 113 °F (-20 to 45) °C

Operating Temperature Range: -40 °F to 113 °F (-40 to 45) °C

Storage Temperature Range: -40 °F to 167 °F (-40 to 75) °C

REGULATORY & VOLUNTARY QUALIFICATION

Certification Listings: MET, CE

Environment: Wet location, IP67

Warranty: 36 month manufacturer's limited warranty
(for covered regions only)

Product
Web Page



WWW.ILUMINARC.COM - INFO@ILUMINARC.COM

Iluminarc reserves the right to make improvements to this product
and its specifications at anytime without notice.

ILUMINARC.
5200 NW 108th Ave.
Sunrise, FL 33351
+1.954.923.3680

ILUMINARC®

ILUMILINE 21g2 IP OPTIC 60x10 RGB

Item Number: 01610557


Client: _____

Project: _____

Date: _____ Type: _____

Ilumiline 21g2 IP Optic 60x10 RGB

- Beam Angle: 60° x 24°
- Field Angle: 99° x 49°



Ilumiline 21g2 IP Optic 60x10 RGB Typical Installation

