

# ILUMINARC®


## LOGIC 4x36

Item Number: 34X36001

Client: \_\_\_\_\_

Project: \_\_\_\_\_

Date: \_\_\_\_\_ Type: \_\_\_\_\_



### CONSTRUCTION & PHYSICAL SPECIFICATIONS

Length: 9.9 in [250 mm]  
Width: 12.7 in [323 mm]  
Height: 2.6 in [67 mm]  
Weight: 5.6 lb [2.5 kg]  
Color: Beige  
Ingress Protection Rating: IP20  
Housing Material: Stamped Steel  
Installation Orientation: Any

### CONTROL SPECIFICATIONS

Control Protocol: USITT DMX-512a  
Control Channels: 1, 2, 3, 4, 6, 9, 12 or 15  
Operating Modes: Selectable personalities

#### RGB Operating Mode:

PERS 1 (1-channel): master dimmer  
PERS 2 (3-channel): red, green, blue  
PERS 3 (4-channel): dimmer, red, green, blue  
PERS 4 (6-channel): dimmer, red, green, blue, color macro, strobe  
PERS 5 (9-channel): dimmer, red, green, blue, color macro, strobe, auto + custom, auto speed  
PERS 6 (12-channel): red, green, blue control of each line  
PERS 7 (15-channel): red, green, blue control of each line, color macro, strobe

#### SpectraWhite™ Operating Mode:

PERS 8 (1-channel): white dimmer  
PERS 9 (2-channel): white control (warm + cool)  
PERS 10 (2-channel): white macro, dimmer  
PERS 11 (3-channel): white control (warm + cool), dimmer  
PERS 12 (5-channel): white control (warm + cool), macro, dimmer, strobe

Stand Alone Control: Yes

Stand Alone Control: Yes

Remote Addresser: N/A

Data Connection: RJ45 to 3-pin DMX in, RJ45 out

Output per Line: 36 - 1 W or 12 - 3 W LEDs

Output Lines: 4

### ELECTRICAL SYSTEM SPECIFICATIONS

Input Voltage: Auto-ranging 100 to 240 VAC, 50/60 Hz (auto-ranging)  
Power and Current: 180 W, 1.5 A @ 120 V  
161 W, 0.7 A @ 230 V  
Power Supply: Electronic internal  
Power Linking: N/A  
Power Connection: 5 ft (1.5 m) IEC cable

### THERMAL SPECIFICATIONS

Cooling: Convection  
Startup Temperature Range: 68 °F to 104 °F [20 to 40] °C  
Operating Temperature Range: 68 °F to 104 °F [20 to 40] °C  
Storage Temperature Range: 68 °F to 104 °F [20 to 40] °C

### REGULATORY & VOLUNTARY QUALIFICATION

Certification Listings: ETL, CE  
Environment: Dry location, IP20  
Warranty: 36 month manufacturer's limited warranty (for covered regions only)

Product  
Web Page



[WWW.ILUMINARC.COM](http://WWW.ILUMINARC.COM) - [INFO@ILUMINARC.COM](mailto:INFO@ILUMINARC.COM)

Iluminarc reserves the right to make improvements to this product  
and its specifications at anytime without notice.

ILUMINARC.  
5200 NW 108th Ave.  
Sunrise, FL 33351  
+1.954.923.3680

## LOGIC 4x36

Item Number: 34X36001

### LOGIC 4x36 Typical Installation

